

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
25 August 2005 (25.08.2005)

PCT

(10) International Publication Number
WO 2005/077293 A2

(51) International Patent Classification⁷: **A61B 19/00**, 5/06

[NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(21) International Application Number:

PCT/IB2005/050451

(74) Agents: **COHEN, Julius, S.** et al.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(22) International Filing Date: 3 February 2005 (03.02.2005)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

04100488.8

10 February 2004 (10.02.2004)

EP

(71) Applicant (for all designated States except US): **KONINKLIJKE PHILIPS ELECTRONICS N.V.** [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventor; and


(75) Inventor/Applicant (for US only): **BOOSTEN, Marcel**

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,

[Continued on next page]

(54) Title: A METHOD, A SYSTEM FOR GENERATING A SPATIAL ROADMAP FOR AN INTERVENTIONAL DEVICE AND A QUALITY CONTROL SYSTEM FOR GUARDING THE SPATIAL ACCURACY THEREOF



(57) Abstract: The invention relates to a method, a system for generating a spatial roadmap for an interventional device and a quality control system for guarding the spatial accuracy thereof. In an embodiment of the system 100 for practicing the invention an X-ray imager 100a is used for acquiring suitable images D_{i-1} , D_i , ..., D_N , showing the volume under examination, comprising the catheters 182a, 182b. These X-ray images are then processed by means of per se known reconstruction method to yield a motion-corrected three-dimensional volume of examination. This volume is then presented by means of suitable user-interface 181 on a display unit 183 together with distal portions of the catheters 182a, 182b provided with detectable markers (for simplicity only one detectable marker per catheter is shown). The motion-corrected three-dimensional image of the target organ 184 is used to construct the motion-corrected target organ-oriented three-dimensional coordinate system which is then used for drawing the spatial roadmap 183 and which is also used to locate a spatial position of a displaceable catheter 185, provided with a further detectable marker 185'. These computations are carried out using computing means 160. The computing means 160 can be further arranged to carry out a further computation comprising a computation of a spatial discrepancy between the envisaged spatial roadmap

183 and the position of the displaceable catheter 185'. In case a substantial discrepancy is signalled and in case the catheters are positioned within the target organ by means of a controllable navigation system 190, the computing means calculates a control signal S to be applied to the navigation system 190 to correct for the mismatch between the spatial roadmap 183 and the position of the displaceable catheter 185. The control unit then applies a correction signal S to the navigation system 190 after which an interventional procedure carries on.



FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations* AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ,

NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

Published:

- *without international search report and to be republished upon receipt of that report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.